

As a manufacturer of safety components, the Cobianchi Lift Components AG is responsible for the design and manufacture of the Cobianchi brake safety catches. In order to be able to make the production, the commissioning and the maintenance and servicing easier for the manufacturers of the lift frameworks and the erection / installation companies, these operating instructions have been established.

In these operating instructions the standard version PC13XX, installed width 180 mm, PC14XX, installed width 180 mm, PC24XX, installed width 200 mm and PC44XX, installed width 240 mm, both respectively with catch shaft and limit switch located within the traverse, are documented. If the installation type you are confronted with deviates from the version described here, then please contact your technical department, resp., your responsible design department.

In the following, you will find important remarks, which if you duly take note of will in all instances contribute to the impeccable installation and operation.

Attached to these operating instructions must be the following 4 drawings:

Drawing No.	Brake Safety Catch Type	Vertical plan, layout, side view
13DA-BA01-1	PC13DA, PC13DO, PC13UP	Assembly drawing FV with item No.
14DA-BA01-1	PC14DA, PC14DO, PC14UP	Assembly drawing FV with item No.
24DA-BA01-1	PC24DA, PC24DO, PC24UP	Assembly drawing FV with item No.
44DA-BA01-1	PC44DA, PC44DO, PC44UP	Assembly drawing FV with item No.

These instructions consist of several pages of text (depending on the language) and 4 drawings. Customer-specific solutions may render deviating erection procedures necessary. The brake safety catches can be installed on top of – or underneath the lift cage taking into consideration the various installed widths and the location of the connecting shaft. For detailed information, please refer to our technical documentation.

Subject to deviations from the standard version described here.

To be duly noted prior to the installation:

The brake safety catch consists of two safety catch heads. On both safety catch heads the respective serial numbers have been burnt-in. These numbers have to correspond to the serial numbers on the two stuck-on adhesive labels as well as to that of the enclosed type nameplate and they have to be able to be correlated with the works serial number of the installation. If this should not be the case, then there is a mix-up and it is absolutely necessary that you make contact with your purchasing department, your stores department or directly with the manufacturer.

The safety catch shaft and the resetting spring system in the case of the brake safety catches bidirectional types PC13DA, PC14DA, PC24DA, PC44DA, single action brake safety catch types PC13DO, PC14DO, PC24DO, PC44DO and upwards braking types PC13UP, PC14 UP, PC24UP, PC44UP are uniformly constructed in the general sense. The following description for this reason can be applied to all the types mentioned.

- 1. Installation** in accordance with the enclosed drawings
 - 1.1.** The installation of the safety catch heads in all instances takes place by means of a fixing plate **12**, on which the base plate **11** is supported and is laterally displaceable. After tightening the screw **7**, it has to be verified, whether the base plate is capable of being laterally displaced and whether it is brought back to its original position at the stop screw **21** by the leaf spring **3**.
 - 1.2.** The fixing plate **12** is bolted on with the gusset plate **5** or else directly to the safety catch frame.
 - 1.3.** The triggering linkage by means of the supporting plate **13** is installed directly on the gusset plate **5** or on the safety catch frame. Please note: The position of the safety catch shaft has to be centred relative to the brake safety catch and the lifter **1** therefore has to be lying horizontally.
 - 1.4.** The force required to hold the triggering lever **1** in its original position is adjustable by means of the threaded rod inside the compression spring **14**. Depending on the application, the spring can be pre-tensioned additionally. The basic setting is at 10 mm pre-tensioning.

2. Connection

- 2.1. Connect the control rope with the rope end connection (rope socket fittings **20**) to the lifter **1** at the control rope attack point.
- 2.2. Wire the brake safety catch switch **17** (230V, 4A) and check its operation.
- 2.3. Adjustment: Laterally align the position of the safety catch heads to the rail. Distance between the fixed brake shoe and the rail: 2 mm.
- 2.4. Verification prior to the commissioning:
 - a) The safety catch heads have to be laterally displaced towards the compression spring **3** and have to be capable of returning to their original position through the spring force.
 - b) The triggering lever **1** has to be displaced in the triggering direction and has to be returned to its original position through the compression spring **14**.

3. Commissioning

3.1. To be duly noted prior to the first safety catch test:

The rail indispensably has to be cleaned of old dirt, rust protection coatings and any coats of paint or varnish. Most suitable for this are cold cleaning agents or brake disk cleaning agents.

In case of oiled rails, only simple machine oil of the viscosity class ISO 68-150 without any high pressure additives must be used (lubricating oil C in accordance with DIN 51517, part 1). Because oils for gearboxes, motors/engines and hydraulic devices frequently contain additives, they are not suitable for this application. -> Duly note the yellow information sticker.

Only PC13XX: It's possible to use oil with any high pressure additives (lubricating oil CLP in accordance with DIN 52517, part 3)

3.2. Triggering forces for engaging the brake safety catch:

These are dependent on the fixing point of the control rope on the control rope lever **1** and **2** are applicable for the installation of our resetting spring system **14** with compression spring under condition that our installation recommendations have been adhered to:

	Distance centre rail – centre control rope			
	140 mm	160 mm	180 mm	
PC13DA, PC13DO, PC13UP PC14DA, PC14DO, PC14UP PC24DA, PC24DO, PC24UP				
Braking upwards	70 N	90 N	110 N	
Catching downwards	100 N	120 N	150 N	
PC44DA, PC44DO, PC44UP	160 mm	180 mm	200 mm	220 mm
Braking upwards	100 N	120 N	140 N	160 N
Catching downwards	100 N	120 N	140 N	160 N



4. Servicing and Maintenance

Once the brake safety catches have been correctly installed, the servicing and maintenance is limited to the checking of:

- 4.1. **The condition of the rail**, in accordance with the above commissioning instructions.
- 4.2. **Triggering linkage**: Synchronous actuation of both safety catch heads, connection without any play through the triggering shaft, free movement of the lifters possible in one or in both directions.
- 4.3. **Return spring**: Present, under pre-tensioning.
- 4.4. **Limit switch 17**: Electrical-, mechanical function and actuation assured.
- 4.5. **Catch heads**: centred, clean, guides of the lift/elevator cage in perfect condition, not expanded/worn.
- 4.6. **Fixing plate**: Freely displaceable base plates **11** on the installation plates **12**.
- 4.7. **Cleanness**: In general and in particular in the case of building elevators / lifts and conversion works make sure, that the safety catch heads are protected against contamination with plaster of Paris/ gypsum, concrete, cement, mortar, grit or similar building materials. Contaminated safety catch heads have to be dismantled and cleaned.

If these simple instructions are complied with, then the safety for the users of the lift / elevator as well as for the erection and installation company can be significantly increased.

Die Bohrungen in den Knotenblechen (Pos. 5) dienen zur Befestigung der Fangvorrichtung im Rahmen.
Die Anzahl der Befestigungsschrauben, sowie die Festigkeit der Verbindung von Traverse und Hängewinkel müssen durch den Rahmenhersteller anwendungsabhängig und konstruktionsbezogen berechnet werden.



FWA: Verbindungsstelle aussenliegend
FWI: Verbindungsstelle innenliegend

Stückzahlen pro Fingervorrichtungspaar		FWA: FWA: Gegenstand		Pos.	Werkstoff	Modell	Gezeichnet	08.12.08	HG
2	2	Schraube M6 zu Blattfeder	22	-	-	1: 25	Kontrolliert	30.08.10	HG
2	2	Einstellschraube M6	21	-	-	-	Gepflicht	30.08.10	DH
1	1	Seilschlössergarnitur	20	-	-	-	Gepflicht	30.08.10	DH
2	2	Scharfschraube	19	-	-	-	Gepflicht	30.08.10	DH
2	2	Anschlaghülse	18	-	-	-	Gepflicht	30.08.10	DH
1	1	Endschalter	17	-	-	-	Gepflicht	30.08.10	DH
-	1	Auslösevierkant kpl.	16	-	-	-	Gepflicht	30.08.10	DH
2	1	Schraube	15	-	-	-	Gepflicht	30.08.10	DH
1	1	Rückzugdruckfedersystem kpl.	14	-	-	-	Gepflicht	30.08.10	DH
2	1	Stützblech 180/200/240mm	13	-	-	-	Gepflicht	30.08.10	DH
2	2	Einbauplatte 180/200/240mm	12	-	-	-	Gepflicht	30.08.10	DH
2	2	Grundplatte	11	-	-	-	Gepflicht	30.08.10	DH
2	2	Führungsschuhplatte 180/200/240mm	10	-	-	-	Gepflicht	30.08.10	DH
1	1	Endschalterführung	9	-	-	-	Gepflicht	30.08.10	DH
1	1	Endschalterarmbau	8	-	-	-	Gepflicht	30.08.10	DH
8	8	Zylinder-schraube	7	-	-	-	Gepflicht	30.08.10	DH
1	1	Auslöser	6	-	-	-	Gepflicht	30.08.10	DH
4	4	Knotenblech	5	-	-	-	Gepflicht	30.08.10	DH
-	1	Hülse kpl.	4	-	-	-	Gepflicht	30.08.10	DH
2	2	Blattfeder 180/200/240mm	3	-	-	-	Gepflicht	30.08.10	DH
2	2	Heber FWA	2	-	-	-	Gepflicht	30.08.10	DH
-	1	Heber FWI	1	-	-	-	Gepflicht	30.08.10	DH

Technische Änderungen vorbehalten

Änderung Datum / Index
30.08.10 / 579

Das Unterrecht auf dieser Zeichnung und allen
Beilagen, die den Empfänger gesetzlich anerkennen
sind weiterhin jederzeit unserer Firm- und
unser schriftlich bezeugter der diese Zeichnung
angegeben EDV kopiert, vervielfältigt und
Grafiken mündlich der zugänglich gemacht werden

Zusammenstellung
zu Betriebsanleitung
FV-Typ: PC130A, PC1300, PC13UP


Sägegasse 5, CH-3110 Münsingen
Tel. ++41 - (0)31/720 50 50
Fax ++41 - (0)31/720 50 51
info@cobran.ch - www.cobran.ch

Cobran Lifferte AG

Ausgabe: 2106.12 / H6


130A-BA01-1

Die Bohrungen in den Knotenblechen (Pos. 5) dienen zur Befestigung der Fangvorrichtung im Rahmen.
Die Anzahl der Befestigungsschrauben, sowie die Festigkeit der Verbindung von Traverse und Hängewinkel müssen durch den Rahmenhersteller anwendungsabhängig und konstruktionsbezogen berechnet werden.



Verbindungsstelle innenliegend
20/20x25 oder 30 nach DIN2395-3
Länge: Stichmass -290

Verbindungsstelle aussenliegend
20/20x25 oder 30 nach DIN2395-3
Länge: Stichmass +110



FWA: Verbindungsstelle aussenliegend
FWL: Verbindungsstelle innenliegend



Technische Änderungen vorbehalten

2	2	Schraube M6 zu Blattfeder	22	-	
2	2	Einstellschraube M6	21	-	
1	1	Seilschlossgarnitur	20	FV-30-1Z	
2	2	Scharfschraube	19	DA-25-1Z	
2	-	Anschlaghülse	18	DA-17-1Z	
1	1	Endschalter	17	DA-05-2	
-	1	Auslösevierkant kpl.	16	DA-03-3Z	
2	1	Schraube	15	44DA-03-1	
1	1	Rückzugdruckfedersystem kpl.	14	44DA-25-1Z	
2	1	Stützblech 180/200/240mm	13	44DA-45-11-31-4	
2	2	Einbauplatte 180/200/240mm	12	44DA-44-11-31-4	
2	2	Grundplatte	11	44DA-43-1	
2	2	Führungsschuhplatte 180/200/240mm	10	44DA-40-11-31-4	
1	1	Endschalterführung	9	44DA-38-2	
1	1	Endschalterverbau	8	44DA-38-1	
8	8	Zylinder-schraube	7	44DA-29-1	
4	1	Auslöser	6	44DA-28-1	
4	4	Knotenblech	5	44DA-19-1Z	
-	1	Hülse kpl.	4	44DA-17-2Z	
2	2	Blattfeder 180/200/240mm	3	44DA-14-11-31-4	
2	-	Heber FWA	2	44DA-01-2Z	
-	1	Heber FWL	1	44DA-01-1	

Stückzahlen pro Fingervorrichtung

Änderung	Datum	Index
200803	388	-
-	-	-
-	-	-
-	-	-
-	-	-
Ausgabe: 2106.12 / H6		
Das Urheberrecht auf dieser Zeichnung und allen Beilagen, die den Empfänger persönlich anvertraut sind, verbleibt jederzeit unserem Firm. Diese werden schriftliche Genehmigung der FWA. Nach dem Kopieren ist die Weitergabe untersagt. Ein Kopieren ohne Kopiert. vervielfältigt und benutzt. Dritten mitteilt, der zugänglich gemacht werden.		
Zusammenstellung		
zu Betriebsanleitung		
FV-Typ: PC14DA, PC14D0, PC14UP		
Sägegasse 5, CH-3100 Münsingen Tel. ++41 - (0)31/720 50 50 Fax ++41 - (0)31/720 50 51 info@cobran.ch - www.cobran.ch		
Cobran Liffelle AG		
Zeichnungsnummer		
alte Zeichnung		
H6		
DH		
250909		
250909		
12.03.03		
Benutzungen		
Modell		
Massstab		
1:25		
Gezeichnet		
14DA-BA01-1		

Die Bohrungen in den Knotenblechen (Pos. 5) dienen zur Befestigung der Fangvorrichtung im Rahmen. Die Anzahl der Befestigungsschrauben, sowie die Festigkeit der Verbindung von Traverse und Hängewinkel müssen durch den Rahmenhersteller anwendungsspezifisch und konstruktionsbezogen berechnet werden.



— FWA: Verbindungswelle aussenliegend

—FWL: Verbindungswelle innenliegend

Technische Änderungen vorbehalten

2	2	Schraube M6 zu Blattfeder	22	-	-
2	2	Einstellschraube M6	21	-	-
1	1	Seilverschlussgarnitur	20	-	FV-30-1Z
2	-	Scharfschraube	19	-	DA-25-1Z
1	1	Anschlaghülse	18	-	DA-17-1Z
-	1	Endschalter	17	-	DA-05-2
2	1	Austösevierkant kpl	16	-	DA-03-3Z
2	1	Schraube	15	-	240A-03-1
1	1	Rückzugdruckfedersystem kpl	14	-	140A-25-1Z
2	1	Stützblech 200 / 240mm	13	-	140A-45-3 / 45-4
2	2	Einbauplatte 200 / 240mm	12	-	240A-44-1 / 44-2
2	2	Grundplatte	11	-	240A-11-2
2	2	Führungsschuhplatte 200 / 240mm	10	-	140A-40-3 / 40-4
1	1	Endschalterführung	9	-	140A-38-2
8	8	Endschalteranbau	8	-	140A-38-1
1	1	Zylinderschraube	7	-	140A-29-1
4	4	Auslöser	6	-	140A-28-1
4	4	Knotenbleih	5	-	140A-19-1Z
-	1	Hülse kpl.	4	-	140A-17-2Z
2	2	Blattfeder 200mm / 240mm	3	-	140A-14-1 / 14-3
2	-	Heber FWA	2	-	240A-01-2Z
-	1	Heber FWL	1	-	240A-01-1


Änderung: Datum / Index					
18.01.10 / 559	-	-	-	-	-
04.11.10 / 586	-	-	-	-	-

Ausgabe: 21.06.12 11:11

Zusammenstellung
zu Betriebsanleitung
FV-Typ: PC24DA, PC24D0, PC24UP



සමබලිතය
Cobianchi Liffteile AG

24DA-BA01-1



Die Bohrungen in den Knotenblechen (Pos. 5) dienen zur Befestigung der Fangvorrichtung im Rahmen.

Die Anzahl der Befestigungsschrauben, sowie die Festigkeit der Verbindung von Traverse und Hängewinkel müssen durch den Rahmenhersteller anwendungsabhängig und konstruktionsbezogen berechnet werden.




— FWA: Verbindungswelle aussenliegend
 — FWL: Verbindungswelle innenliegend

Technische Änderungen vorbehalten

2	2	Schraube M6 zu Blattfeder	22	-	-
2	2	Einstellschraube M6	21	-	-
1	1	Seilschlossgarnitur	20	-	FV-30-1Z
2	2	Schloßschraube	19	-	DA-25-1Z
2	-	Anschlußhülse	18	-	DA-17-1Z
1	1	Endschalter	17	-	DA-05-2
-	1	Auslösevierkant Kpl.	16	-	DA-03-3Z
2	1	Schraube	15	-	440A-03-1
1	1	Rückzugdruckfedersystem Kpl.	14	-	140A-25-1Z
2	1	Stützblech	13	-	440A-45-1
2	2	Einbauplatte	12	-	440A-44-1
2	2	Grundplatte	11	-	440A-43-1
2	2	Führungsschuhplatte	10	-	440A-40-1
1	1	Endschalterführung	9	-	140A-38-2
1	1	Endschalteranbau	8	-	140A-38-1
8	8	Zylinder-schraube	7	-	440A-29-1
1	1	Auslöser	6	-	140A-28-1
4	4	Knotenblech	5	-	440A-19-1
-	1	Hülse kpl.	4	-	140A-17-2Z
2	2	Blattfeder	3	-	440A-14-1
2	-	Heber FWA	2	-	440A-01-2Z
-	1	Heber FWL	1	-	440A-01-1

Änderung (Datum / Index)	Ausgabe: 21.06.12 / H5
20.08.03 / 389	



44DA-BA01-1